


Wireless and Wired Bridging using Vlan.

(A case study at Electrical Engineering UBAYA).

Topics of Discussion

- Virtual LAN (VLAN)
- Wired and Wireless Trunk System (Bridge, WDS, Repeater, Tunnel)
- Implementation Vlan @ EE Ubaya
 - Discussion



About Me

(yohanesgunawan@staff.ubaya.ac.id)



- ◆ My Name is Yohanes Gunawan Yusuf, from Indonesia. I am a full time lecturer of University of Surabaya (Ubaya).
- ◆ I have learn and teach in Department of Electrical Engineering (EE) and IT since 1986.
- ◆ MikroTik Academy Trainer for EUTC with certifications: MTCNA, MTCRE, MTCWE, MTCTCE and MTCINE

University of Surabaya (Ubaya)



Universitas Surabaya (Ubaya)







UBAYA
UNIVERSITAS SURABAYA

Elektro Ubaya

(te.ubaya.ac.id)

[f Teknik Elektro Ubaya](#)

[@teknikelektroubaya](#)

[te.ubaya.ac.id](#)

[Teknik Elektro Ubaya](#)

INDUSTRIAL ROBOTIC
DESIGN
TELECOMMUNICATION
NETWORK **DESIGN**

MikroTik
MTCNA




Objective

- ◆ To help you understand fundamental of Virtual Local Area Network (VLAN) and implementation in MikroTik router
- ◆ To explain a few example of implementation of Vlan in Wireless dan Wired Trunk
- ◆ To show the implementation VLAN in Electrical Engineering (EE) - Ubaya


VLAN (Virtual LAN)

- ◆ VLAN is a **Layer 2** method that allows **multiple Virtual LANs** on a **single physical interface**.
- ◆ You can also transport VLANs over **wired** and **wireless** links and put multiple VLAN interfaces on a single wireless interface



VLAN

- ◆ Each VLAN is treated as a separate subnet. It means that by default, a host in a specific VLAN cannot communicate with a host that is a member of another VLAN, although they are connected in the same switch.




Why VLAN ?

- ◆ We can create multiple LAN in a single physical interface, so we will have multiple broadcast domain in a single physical interface
- ◆ We can manage the local network more simple and manage the different network in one single interface
- ◆ We can create multiple vlan-id in one interface (Trunk) OR multiple interface for one vlan-id (Access)


IEEE 802.1Q

- ◆ IEEE 802.1Q is a standardized encapsulation protocol that defines how to insert (tagged) a four-byte VLAN identifier into Ethernet header.
- ◆ RouterOS supports up to 4095 VLAN interfaces, each with a unique VLAN ID, per interface (exception: 0,1 and 4095)



IEEE 802.1Q

Tagged






UnTagged

Ether Type: 0x0800 (IP4) , 0x8100 (802.1Q)

VLAN Access and Trunk

A trunk **carries Tagged** packets between switches and/or router.

TRUNK (VLAN 10, VLAN 20, VLAN 30)



ACCESS

ACCESS

ACCESS

VLAN 10 20 30


VLAN10 20 30

VLAN10 20 30


Access **carries Untagged** packets to end devices or host (PC, laptop, Servers, etc)

VLAN Access and Trunk


Tagged Vlan ID



ACCESS
VLAN 10 20 30






ACCESS
VLAN10 20 30



ACCESS
VLAN10 20 30


VLAN Access and Trunk

TRUNK (VLAN 10, VLAN 20, VLAN 30)



Untagged VLAN ID

Tagged and Untagged Vlan ID




- ◆ Vlan ID: Tagged on Trunk, then Untagged on Access

How to VLAN?


1. Create bridges for Trunk and bridges for each Access
2. Add Interfaces VLAN on the Trunk Bridge and put ethernet (tagged) port into Trunk Bridge Port
3. Add untagged vlan interface and ethernet (untagged) ports into Access Bridges Port.

1) Create Bridges




Create bridges for Trunk and bridges for each Access

```
/interface bridge  
add fast-forward=no name=bridge-trunk  
add fast-forward=no name=bridge-vlan200  
add fast-forward=no name=bridge-vlan300  
add fast-forward=no name=bridge-vlan400
```




2) Create VLAN @BridgeTrk




Add Interfaces VLAN on the Trunk Bridge and put ethernet (tagged) port into Trunk Bridge Port

```
/interface vlan  
add interface=bridge-trunk name=eth2-vlan200 vlan-id=200  
add interface=bridge-trunk name=eth2-vlan300 vlan-id=300  
add interface=bridge-trunk name=eth2-vlan400 vlan-id=400  
  
/interface bridge port  
add bridge=bridge-trunk interface=ether2
```




3) Untagged VLAN @BridgeAcc



Add untagged vlan interface and ethernet (untagged) ports into Access Bridges Port.



```
/interface bridge port  
  
add bridge=bridge-vlan200 interface=eth2-vlan200  
add bridge=bridge-vlan200 interface=ether6  
  
add bridge=bridge-vlan300 interface=eth2-vlan300  
add bridge=bridge-vlan300 interface=ether7  
  
add bridge=bridge-vlan400 interface=eth2-vlan400  
add bridge=bridge-vlan400 interface=ether8
```



Bridge VLAN Filtering


(since RouterOS 6.41 AND support Hardware Offload)

1. Create a bridge with disabled vlan-filtering (no)
2. Add Bridge Ports and specify PVID for VLAN access ports to assign their untagged traffic to the intended VLAN.
3. Add Bridge VLAN entries and specify tagged and untagged ports in them.
4. In the end, when VLAN configuration is complete, enable vlan-filtering.



<https://wiki.mikrotik.com/wiki/Manual:Interface/Bridge>

Bridge VLAN Filtering



```
/interface bridge  
add name=bridge1 vlan-filtering=no
```

```
/interface bridge port  
add bridge=bridge1 interface=ether2  
add bridge=bridge1 interface=ether6 pvid=200  
add bridge=bridge1 interface=ether7 pvid=300  
add bridge=bridge1 interface=ether8 pvid=400
```

```
/interface bridge vlan  
add bridge=bridge1 tagged=ether2 untagged=ether6 vlan-ids=200  
add bridge=bridge1 tagged=ether2 untagged=ether7 vlan-ids=300  
add bridge=bridge1 tagged=ether2 untagged=ether8 vlan-ids=400
```

```
/interface bridge set bridge1 vlan-filtering=yes
```


Interface <bridge1>				
General	STP	VLAN	Status	Traffic
<input type="checkbox"/> VLAN Filtering				
PVID: 1				

Reading Suggestion

- ◆ https://wiki.mikrotik.com/wiki/Manual:Interface/Bridge#Bridge_VLAN_Filtering (edited 8 October 2018)
- ◆ https://wiki.mikrotik.com/wiki/Manual:Interface/Bridge#Management_port (edited 8 October 2018)
- ◆ https://wiki.mikrotik.com/wiki/Manual:Layer2_misconfiguration (edited 22 Agustus 2018)
- ◆ Youtube:https://www.youtube.com/watch?v=ZM_Mpza-O7_w (VLAN processing in New bridge implementation by: Andis Arins, April 2018)

Hybrid VLAN Ports


- ◆ An Hybrid Vlan port is a special mode that allow untagged and tagged packets on the same port.




```
/interface bridge vlan
add bridge=bridge1 tagged=ether2,ether7,ether8 untagged=ether6 vlan-ids=200
add bridge=bridge1 tagged=ether2,ether6,ether8 untagged=ether7 vlan-ids=300
add bridge=bridge1 tagged=ether2,ether6,ether7 untagged=ether8 vlan-ids=400
```

Inter VLAN Routing

- Routing process between VLANs is called Inter-VLAN Routing. Communication between VLAN must be Routed.
- Configure VLAN interfaces on the **bridge1** to allow handling of tagged VLAN traffic at routing level



Wired Trunk



WIRED TRUNK:
Ether 1: Vlan ID
110,120,130

ACCESS PORTS Vlan:
Wlan 1:
110: 192.168.110.0/24
Ether 2:
120: 192.168.120.0/24
Ether 3-5:
130: 192.168.130.0/24

Wireless Trunk



WIRELESS TRUNK:

Wlan1 : VLan 110,120,130:
192.168.100.0/24

ACCESS PORTS Vlan:

Ether 1:

110: 192.168.110.0/24

Ether 2:

120: 192.168.120.0/24

Ether 3-5:

130: 192.168.130.0/24

1) Create Bridges

Create bridges for trunk and bridges for each access VLAN

```
/interface bridge  
add fast-forward=no name=bridge1trunk  
add fast-forward=no name=bridge2vlan110  
add fast-forward=no name=bridge2vlan120  
add fast-forward=no name=bridge2vlan130
```

2) Create VLAN @BridgeTrk

Add Interfaces VLAN on the Trunk Bridge and put ethernet/wlan (tagged) port into Trunk Bridge Port
Give Name and unique VLAN ID (ex:110, not 0,1 or 4095)

```
/interface vlan
add interface=bridge1trunk name=vlan110 vlan-id=110
add interface=bridge1trunk name=vlan120 vlan-id=120
add interface=bridge1trunk name=vlan130 vlan-id=130
/interface bridge port
add bridge=bridge1trunk interface=wlan1
```

TRUNK

3) Untagged VLAN @BridgeAcc

Add untagged vlan interface and ethernet (untagged) ports into Access Bridges Port.

/interface bridge port

```
add bridge=bridge2vlan110 interface=vlan110
add bridge=bridge2vlan120 interface=ether2
add bridge=bridge2vlan120 interface=vlan120
add bridge=bridge2vlan130 interface=ether3
add bridge=bridge2vlan130 interface=vlan130
add bridge=bridge2vlan130 interface=ether4
add bridge=bridge2vlan130 interface=ether5
```

ACCESS

VLAN in MikroTik

The screenshot displays four windows from the MikroTik Winbox interface:


- Interface List:** Shows a list of interfaces including bridge1trunk, vlan110, vlan120, and vlan130.
- Bridge:** Shows the bridge configuration with multiple ports assigned to different bridges.
- Interface <vlan110>:** A detailed configuration window for VLAN 110. The **VLAN ID:** field is set to 110 and the **Interface:** field is set to bridge1trunk. Both of these fields are highlighted with a red rectangle.
- Address List:** Shows a list of IP addresses and their corresponding networks and interfaces.

A red arrow points from the "Interface" tab in the Interface List window to the "VLAN ID" field in the Interface <vlan110> window. Another red arrow points from the "Interface" field in the same window to the "Interface" tab in the Bridge window.

#	Interface	Bridge	Horizon
0	bridge1trunk	wlan1	
1	ether7	bridge2vlan110	IH
2	vlan110	bridge2vlan110	
3	ether2	bridge2vlan120	
4	vlan120	bridge2vlan120	
5	ether3	bridge2vlan130	I
7	ether4	bridge2vlan130	I
8	ether5	bridge2vlan130	I
6	vlan130	bridge2vlan130	


Address	Network	Interface
192.168.100.99/24	192.168.100.0	wlan1
192.168.110.1/24	192.168.110.0	bridge2vlan110
192.168.120.1/24	192.168.120.0	bridge2vlan120
192.168.130.1/24	192.168.130.0	bridge2vlan130

Wireless Trunk



- ◆ Wireless Bridge (AP-Bridge, Station-Bridge) -> bridge to ethernet, etc
- ◆ Wireless Distribution System -> Roaming
- ◆ Wireless Repeater -> Extend Range
- ◆ Tunnel (EoIP, PPTP with BCP) -> Secured Tunneling

Wireless Bridge



R1

Act as usual **AP Bridge** with specific Band Frequency, SSID and Security Profile
Bridge between wlan and ethernet

R2

Act as **Station bridge** for selected Access Point (AP)
Bridge between wlan and ethernet


Bridge VLAN on Wireless Bridge

It is done by creating Vlan Interface (Vlan110, Vlan 120, Vlan 130) on Wireless-Bridge (ie: bridge2wlan-ether)

```
/interface vlan  
add interface=bridge2wlan-ether name=vlan110 vlan-id=110  
add interface=bridge2wlan-ether name=vlan120 vlan-id=120  
add interface=bridge2wlan-ether name=vlan130 vlan-id=130
```

```
/interface bridge port  
add bridge=bridge2wlan-ether interface=wlan1
```


WDS (Master - Slave)



- ◆ WDS Master: as AP-Bridge with specific SSID, Band, Freq and Security Profile
- ◆ WDS Slave: same as ap-bridge, but scan for AP with the same ssid and establishes WDS link.
- ◆ WDS Master and Slave **MUST BE Bridge** into WDS Default Bridge


Create WDS Bridge

- ◆ Create WDS Default bridge with specific name, like: bridge2wds for both Master WDS and Slave WDS




Create WDS Master

- ◆ Enable Wlan as AP-Bridge with specific Security Profile
- ◆ In tab WDS, set WDS mode Static
- ◆ Set WDS Default Bridge to created bridge before (ie: bridge2wds).




Create WDS Master

- ◆ In Wireless Menu at Wifi Interface Add (+) WDS Interface on Wlan as Master Interface
- ◆ Fill WDS Address for WDS Slave MAC Address




Create WDS Slave

- ◆ Enable Wlan as WDS-Slave
- ◆ Tab WDS, set WDS mode Static
- ◆ Set WDS Default Bridge to created bridge before (ie: bridge2wds).



Create WDS Slave

- ◆ In Wireless Menu at Wifi Interface Add (+) WDS Interface on Wlan as Master Interface
- ◆ Fill WDS Address for WDS Master MAC Address




RSA (Running, Slave, Active) WDS

Interface List								
Interface		Interface List		Ethernet	EoIP Tunnel	IP Tunnel	GRE Tunnel	VLAN
								Detect Internet
	Name	Type		Actual MTU	L2 MTU	Tx	Rx	T
S	ether15	Ethernet		1500	1588	0 bps	0 bps	
S	ether16	Ethernet		1500	1588	0 bps	0 bps	
S	ether17	Ethernet		1500	1588	0 bps	0 bps	
S	ether18	Ethernet		1500	1588	0 bps	0 bps	
S	ether19	Ethernet		1500	1588	0 bps	0 bps	
S	ether20	Ethernet		1500	1588	0 bps	0 bps	
S	ether21	Ethernet		1500	1588	0 bps	0 bps	
S	ether22	Ethernet		1500	1588	0 bps	0 bps	
S	ether23	Ethernet		1500	1588	0 bps	0 bps	
S	ether24	Ethernet		1500	1588	0 bps	0 bps	
S	sfp1	Ethernet		1500	1588	0 bps	0 bps	
R	wlan1	Wireless (Atheros AR93...		1500	1600	525.7 kbps	25.5 kbps	
RSA	wds1	WDS		1500	1600	525.7 kbps	25.5 kbps	

Bridge VLAN on WDS

- ◆ It is done by creating Vlan Interface (Vlan10, Vlan 20, Vlan 30) on WDS Bridge Default (ie: bridge2wds)



Wireless Repeater



R1

Act as usual AP Bridge with specific Band Frequency, SSID

R2

Set wlan1 as Station bridge for selected Access Point (AP)
Create Virtual AP (wlan2) from master interface wlan1
Bridge between wlan1 and wlan2 as Trunk .OR.
Bridge wlan2 to Access Bridge as Access Port

Bridge VLAN on Wireless Repeater

It is done by creating Vlan Interface (Vlan110, Vlan 120, Vlan 130) on Wireless Repeater-Bridge (ie: bridge1wireless)

```
/interface vlan  
add interface=bridge1wireless name=vlan110 vlan-id=110  
add interface=bridge1wireless name=vlan120 vlan-id=120  
add interface=bridge1wireless name=vlan130 vlan-id=130
```

```
/interface bridge port  
add bridge=bridge1wireless interface=wlan1  
add bridge=bridge1wireless interface=wlan2
```

Wireless Tunnel



```
/interface bridge  
add fast-forward=no name=bridge3eoip  
/interface eoip  
add mac-address=02:A7:59:B2:DB:CB name=eoip-tunnel1  
remote-address=192.168.80.1 tunnel-id=111  
/interface vlan  
add interface=bridge3eoip name=vlan300 vlan-id=300  
/interface bridge port  
add bridge=bridge2vlan300 interface=eoip-tunnel1  
add bridge=bridge2vlan300 interface=ether3
```

Bridge VLAN on Wireless Tunnel

It is done by creating Vlan Interface (ie: Vlan 300) on Wireless Tunnel-Bridge (ie: bridge3eoip)

```
/interface vlan  
add interface=bridge3eoip name=vlan300 vlan-id=300
```

```
/interface bridge port  
add bridge=bridge2vlan300 interface=eoip-tunnel1  
add bridge=bridge2vlan300 interface=ether3
```

Implementation @ EE Ubaya


- ◆ There are 3 building TA, TB, TC and Outdoor
- ◆ Between building connected wired and wirelessly.
- ◆ There is a or several Main Router Board (RB) or Switch in each building
- ◆ From the Main RB is connected to Ethernet to some extended RB or switches and several APs

Wireless Scope Area





The Implemented Topology



Hardware Type

- ◆ CRS 226-24G-2S-IN
- ◆ CRS 125-24G-1S-2HnD-IN
- ◆ RB 2011UiAS-2HnD-IN
- ◆ RB 952 Ui-5ac2nD
- ◆



VLAN ID Planning

- ◆ VLAN 10: used for **faculty** management staff and or laboratory administrator.
- ◆ VLAN 20: used for **lecturers** in TA, TB and TC buildings
- ◆ VLAN 30: used for **student** in **laboratory or class** in TA, TB and TC building
- ◆ VLAN 80, 81: used for **roaming student** and or **outdoor gazebo area**

VLAN BRIDGES Planning

- ◆ For TRUNK

Bridge-Trunk : Ether1-2

Bridge-TrunkWL : Wlan1,2

- ◆ For ACCESS


BridgeVlan10: Ether 3-8 : VLAN 10

BridgeVlan20: Ether 9-16 : VLAN 20


BridgeVlan30: Ether 17-24 : VLAN 30

BridgeVlan8x: Wlan1,2 : VLAN 80, 81


VLAN ACCESS Port Planning




VLAN ACCESS Port Planning



VLAN ACCESS Port Planning



VLAN ACCESS Port Planning




VLAN ACCESS Port Planning

WIRELESS ACCESS (VLAN 80 or VLAN 81)



ROUTERs TA




WIRED ACCESS

VLAN10 20 30

EUTC

ROUTERs TB




WIRED ACCESS

VLAN10 20 30

MUM Yogyakarta 19-20 Oct 2018

ROUTERs TC



VLAN10 20 30


59

VLAN TRUNK Planning

WIRELESS TRUNK (VLAN 80, VLAN 81)




ROUTERs TA




WIRED TRUNK

ROUTERs TB




VLAN 10, 20 30

ROUTERs TC



WIRED TRUNK


VLAN Overall Planning




VLAN 10, 20, 30 Plan

- ◆ Use for indoor or internal building users (student, laboratory, lecturer, administration staff)
- ◆ Use: **Wired trunk** (SFP and Ethernet trunk)
- ◆ Router TB2 as **Main Router**: Wan (ether1-2) Trunk (ether3-8)
- ◆ Router TAs, TBs, TCs, Outdoors as **Access Router**: Trunk (ether1-2), Access Vlan (10: ether 3-8, 20: ether 9-16, 30: ether 17-24)

Router TB2 (Main Router)



Router TAs, TBs, TCs (Access)



ACCESS VLAN 10


20

30

VLAN 80, 81 Plan

- ◆ Only use for Roaming Student between building TA, TB and TC (vlan 80 and 81)
- ◆ Use: Wireless Trunk - Repeater, AP Bridge, WDS (Master - Slave)
- ◆ Router TB: as WDS Master (AP-Bridge)
- ◆ Router Outdoor Gazebo: as WDS Slave
- ◆ Router Indoor Wireless: AP-Bridge, Station-Bridge, Repeater

VLAN Planning (Vlan 80, 81)



ROUTER TB

AP BRIDGE

WDS and/or Repeater

ROUTER GAZ1



WDS SLAVE

ROUTER GAZ2




REPEATER

ROUTER GAZ3



WDS SLAVE

Main Router (TB2) Configuration




Main Router (TB2) Configuration

- 1) To be able to forward tagged packet, we need to create trunk bridge and access bridge.

/interface bridge

```
add fast-forward=no name=bridge-trunk  
add fast-forward=no name=bridge-trunkwl  
add fast-forward=no name=bridgevlan10  
add fast-forward=no name=bridgevlan20  
add fast-forward=no name=bridgevlan30  
add fast-forward=no name=bridgevlan80  
add fast-forward=no name=bridgevlan81
```



Bridges for
TRUNK


Bridges for
ACCESS

Main Router (TB2) Configuration

2a) Create VLAN interface in the trunk bridge

```
/interface vlan
```

```
add interface=bridge-trunk name=vlan10 vlan-id=10
add interface=bridge-trunk name=vlan20 vlan-id=20
add interface=bridge-trunk name=vlan30 vlan-id=30
add interface=bridge-trunk name=vlan80 vlan-id=80
add interface=bridge-trunk name=vlan81 vlan-id=81
add interface=bridge-trunkwl name=vlan80w vlan-id=80
add interface=bridge-trunkwl name=vlan81w vlan-id=81
```



Wired
Trunk


Wireless
Trunk

Main Router (TB2) Configuration

2b) Add ethernet (ether3-8) port that we want to forward the VLAN in the trunk bridge

/interface bridge port

```
add bridge=bridge-trunk interface=ether3
add bridge=bridge-trunk interface=ether4
add bridge=bridge-trunk interface=ether5
add bridge=bridge-trunk interface=ether6
add bridge=bridge-trunk interface=ether7
add bridge=bridge-trunk interface=ether8
```



Ports
for
TRUNK

Main Router (TB2) Configuration

3a) Add ethernet (9-16) interfaces to the Vlan 20 access bridges and ethernet port (17-24) for Vlan 30

/interface bridge port


add bridge=bridgevlan20 interface=vlan20

add bridge=bridgevlan20 interface=ether9

add bridge=bridgevlan20 interface=ether10

.....

add bridge=bridgevlan20 interface=ether16




Ports for
ACCESS
(ex: vlan20)

Main Router (TB2) Configuration

3b) Add ethernet (9-16) interfaces to the Vlan 20 access bridges and ethernet port (17-24) for Vlan 30

/interface bridge port

```
add bridge=bridgevlan30 interface=vlan30
add bridge=bridgevlan30 interface=ether17
add bridge=bridgevlan30 interface=ether18
.....
add bridge=bridgevlan30 interface=ether24
```



Ports
for
ACCESS
(ex: vlan30)

DHCP Configuration

- ◆ Give IP for each bridgevlan access then
- ◆ Create DHCP Server setup for interface bridgevlan10, 20, 30 and 80, 81 with specific IP Pool addresses.

```
/ip dhcp-server
add address-pool=dhcp_pool1 disabled=no interface=bridgevlan10
name=dhcp1
add address-pool=dhcp_pool2 disabled=no interface=bridgevlan20
name=dhcp2
.....
add address-pool=dhcp_pool5 disabled=no interface=bridgevlan81
name=dhcp5
```

Network Configuration

- ◆ Make a masquerade NAT action output to WAN bridge interface.

```
/ip firewall nat  
add action=masquerade chain=srcnat out-  
interface=bridge1wan
```

- ◆ Make necessary Firewall need.
- ◆ Make a default gateway route and IP Route for internal VLAN route if necessary.


Centralized Network Management

- ◆ Centralized DHCP Server
- ◆ Centralized QoS (Simple Que, HTB)
- ◆ Centralized Route Management (Policy Routing, Route-Rules)
- ◆ Centralized Firewall (NAT, Filter, Mangle)
- ◆ Centralized Wireless Management (CapsMan)

Access Router Configuration (TAs, TCs, TBs)

Trunk: ether1, Access: ether 2-8 (10), 9-16(20),
17-24(30)


```
/interface vlan
add interface=bridge-trunk name=vlan10 vlan-id=10
add interface=bridge-trunk name=vlan20 vlan-id=20
add interface=bridge-trunk name=vlan30 vlan-id=30
add interface=bridge-trunk name=vlan20 vlan-id=80
add interface=bridge-trunk name=vlan30 vlan-id=81
/interface bridge port
add bridge=bridge-trunk interface=ether1
```



Access Router Configuration (TAs, TCs, TBs)

Trunk: ether1, Access: ether 2-8 (10), 9-16(20),
17-24(30)

```
/interface bridge port
add bridge=bridgevlan10 interface=vlan10
add bridge=bridgevlan10 interface=ether2
.....
add bridge=bridgevlan10 interface=ether8
.....
add bridge=bridgevlan30 interface=vlan30
add bridge=bridgevlan30 interface=ether17
.....
add bridge=bridgevlan30 interface=ether24
```



Ports
for
ACCESS 10 20 30

Access Router Configuration (GAZs, Outdoors)

Trunk: wlan1, WDS: Master-Slave

Create Vlan80, 81 on WDS Bridge

```
/interface bridge
add fast-forward=no name=bridge2wds
/interface bridge port
add bridge=bridge2wds interface=wlan1
/interface vlan
add interface=bridge2wds name=vlan80 vlan-id=80
add interface=bridge2wds name=vlan81 vlan-id=81
/interface wireless wds
add disabled=no master-interface=wlan1 name=wds1 wds-
address=D4:CA:6D:0C:26:CA
add disabled=no master-interface=wlan1 name=wds2 wds-
address=4C:5E:0C:32:76:4F
.....
```



Conclusion & Discussion

- ◆ Bridging vlan (wired and wireless) makes network management easier and centralized.
- ◆ VLAN could be put or attached in bridge or physical interface.
- ◆ When you add an interface to a bridge, the bridge becomes the master interface and all bridge ports become slave ports, this means that all traffic that is received on a bridge port is captured by the bridge interface and all traffic is forwarded to the CPU using the bridge interface instead of the physical interface.

Conclusion & Discussion

- ◆ With bridges, it is easy to show and manage the trunk port or access port.
- ◆ Always **disable VLAN filtering** first, before you are sure about your VLAN setting !
- ◆ Always **give the specific IP to the bridges** for ease of maintenance and trouble-shooting.
- ◆ **Bridging in wireless**, we should use station-bridge or bridge mode, don't use station only mode.
- ◆ The **disadvantage of wds and repeater link** is the reduction of the throughput on the wireless side.

References

- ◆ <https://wiki.MikroTik.com/wiki/Manual:Interface/VLAN>
- ◆ https://wiki.mikrotik.com/wiki/Manual:Interface/Bridge#Bridge_VLAN_Filtering
- ◆ https://wiki.mikrotik.com/wiki/Manual:Layer2_misconfiguration
- ◆ https://wiki.mikrotik.com/wiki/Manual:Interface/Bridge#Management_port
- ◆ https://wiki.mikrotik.com/wiki/Vlans_on_Mikrotik_environment
- ◆ https://en.wikipedia.org/wiki/Wireless_distribution_system
- ◆ https://wiki.MikroTik.com/wiki/WDS_repeater_example

Credit to

- ◆ MikroTik and MUM Yogyakarta 2018 Committee
- ◆ Telecommunication and Network Design Laboratory (TND - Ubaya)
- ◆ Mr. Herry Darmawan and Team
- ◆ Elektro UBAYA Training Center (EUTC)
- ◆ My Colleagues

Thank you